

HOLLYWOOD MOTOR SPORTS GUT & GO MIDSIZE/COMPACT

80n and newer front wheel drive cars only
If it cannot be built in a couple days your over building!
If it isn't in the rules you cannot do it!

Drivers:

Must wear long pants, shirt and shoes
Must wear approved helmet and eye protection during competition.

Car Preparation:

**Must completely remove all air bags including charges by unbolting complete airbag.
Must have working seat belt for driver.
Must strip all lights, glass, plastic trim, bumper covers and anything else that can fall off during competition. Interior: must remove carpeting, head liner, rear seat, and any loose debris inside car. Trailer hitches must be Removed
Windshields optional

TRUNKS, AND DOORS:HOODS,

Up to 6 chains, cable, or wire may be used to secure hood, 4 in trunk, and doors. 3/8" max chain size or 2 strands of wire. Hoods can be moved forward but must stay on at least 2 hinges, or if you don't run hinges 10" max forward. Trunk lids must remain on hinges, you may tuck 50% of lid in trunk, you may also completely remove. You may V trunk and speaker deck up to 8" down from factory position to increase vision. Factory hinges do not count towards 4 spots.

Must have 12"x12" hole cut in hood in case of fire. Headers are ok
Recommended relocate battery to front floor of vehicle,[not mandatory] secured in a wood or angle iron steel enclosure. Enclosure bolted or chains to passenger front floor. Battery must be covered by floor mat.

We recommend relocating a steel (only) boat style gas tank or aftermarket, built tank with fittings up to 6 gallons off recommended rear seat bar, or on the floor where your feet go on passenger side of vehicle. Chained or bolted to floor. We will allow cars, equipped with factory tank ahead of rear axle with limited rust to leave in stock location.

We recommend a rear seat bar. Mounted midway up rear seat horizontally from pillar-door to pillar- door. May be welded or bolted in but must pass safety.

Stock DOT, street tire and rims only. No tractor lug, nothing heavier than 6 ply. May be doubled and tubed or use flaps on outside only.

BUMPERS

If you have a plastic front bumper you may swap with a bumper off a midsize, only, front wheel drive 80s and newer car. Do not shorten or modify any more than necessary to get bumper to bolt to car. Both bumpers may have 2 chains from bumper to core support, in front or to tail light area in rear. 3/8" max chain. 24" long max. 1 link bolted or welded for each spot. No added metal ,concrete,etc factory stock

Suspension

No height above 20" stock suspension parts. If pre bending rear bumper must remain under 20" high. Struts must bounce

All cars must be safe at all times to run. Do not alter suspension, or engine mounts etc. This is a strict off the street class. No excessively rusty cars will be permitted to run!

You may run safety bars as in semi stock class. No Rear window bar.

BODY PANELS

No creasing of any body panels A 3 inch tweak can be done to back end to prevent car from going down in one hit anymore go back to pit area.

This is gut n go don't do anything more than that.

Rule question 9204102008